

ecomax[™]
by **HOBART**



Flight-Type Dishwasher

ecomax[™] **900**
by **HOBART**



Technical Data:

Plates * capacity / h		Conveyor Speed (m/min.)	Mono-Rinse Water consumption (l/h)	Duo-Rinse Water consumption (l/h)	Recommended choice of models	Total length L (in mm)	Entry Z (in mm)	Exit A (in mm)	Conv. motor (kW)
Speed 1*	Speed 2*								
1530	2050	0,7 / 0,95	400	320	0-L-DL3	3800	440	800	0,25
1530	2050	0,7 / 0,95	400	320	1-L-DL3	4100	740	800	0,25
1860	2270	0,85 / 1,05	400	320	1-A-DL3	4100	440	800	0,25
1860	2270	0,85 / 1,05	400	320	2-A-DL3	4400	740	800	0,25

* Plate size 24-26cm diameter.

Recom- mended choice of models	Main Wash				Mono-Rinse / Duo-Rinse					Dryer		
	Pump loading (kW)	Pump capacity (l/min.)	Tank volume (l)	Tank heating (kW)	Rinse pump (kW)	Revol. Pump (kW)	Booster Standard (kW)*	Booster Standard (kW)**	Booster Heat- recovery (kW)*	Fan (kW)	Air circul. (m³/h)	Heating (kW)
0-L-DL3	1,5	400	125	18	0,55	0,18	36 30	18 15	21 18	1,00	2200	6
1-L-DL3	1,5	400	125	18	0,55	0,18	36 30	18 15	21 18	1,00	2200	6
1-A-DL3	2,2	660	125	18	0,55	0,18	36 30	18 15	21 18	1,00	2200	6
2-A-DL3	2,2	660	125	18	0,55	0,18	36 30	18 15	21 18	1,00	2200	6

* Cold water supply (15°C) for rinse. ** Warm water supply 45°C.

