Food Waste Disposal

500, 700 & 800 Series Food Waste Disposers

MC



525

Technical Specification

For shipping specifications please see pages 25-26

526

Choice of 0.55, 1.1 and 2.2kW reversible motors • Ideal for use in small to medium-size kitchens • Under-sink, welded-in or free-standing models

These IMC Food Waste Disposers are the number one choice for operators of small to medium-size kitchens, who demand proven reliability and quiet efficiency. The 500 Series consists of three models offering a choice of installation methods. Units can be mounted under the sink, welded into tabling or used as free-standing machines. Fitted

523

with a 0.55kW motor and special alloy cutting elements, the 500 Series disposers deal effortlessly with waste from kitchens in establishments such as fast food outlets, small restaurants and hospital wards.

	523	525	526
Capacity (nominal)	100kg per hour	150kg per hour	150kg per hour
Meals	200 per day max	300 per day max	300 per day max
Motor	0.55kW		
Voltages	220/240-1-50 or 380/420-3-50		
Motor Controller	Wall mounted	Wall mounted	Integral
Fuse Ratings	1 phase: 15A 3 phase: 5A		
Mounting	Sink Outlet	Welded	Free standing
Water Connection	from storage cistern and not from rising main to meet UK water regulations. Minimum pressure (head) of 0.4 bar (4m).		
Water Control	Manual	Solenoid Valve	
Water Consumption	11-14 litres per min		
Waste Connection	42mm copper or plastic pipe to be installed with Por S trap laid to a minimum fall of 1 in 7		
Electrical Connection	From a fused isolator switch into the controller Model 526 is supplied with 2.5m mains cable wired into the integral controller		
	FEATURES AND OPTIONS		
Safety Interlock	N/A	~	
Options	Stainless steel side panels for 526		

