

Eco-Line, plug ready cabinets



Eco-Line cabinets: large storage capacity at a small investment.

Highly efficient bottle cooling cabinets available in anthracite skin plate or stainless steel finish and solid doors or glass doors.

Insulation: polyurethane 40 mm. Standard features: Digital electronic thermostat, automatic defrost, exchangeable magnetic gaskets and 2 shelves per door section.

Plug ready under counter cooling cabinets

Climate class N: functions optimally in surrounding temperatures of up to 32°C / 90°F.
Cooling capacity: 463 W* (8,8 cc) - Voltage range: 220-240 V / 50Hz / 1~ -
Temperature range: +2°C / +12°C - Digital electronic thermostat

Solid Doors...

2 Doors, anthracite exterior

- Internal volume: 325 L
- Bottle capacity: 294 x 33 cl
- Power consumption: 370 W*
- Dimensions W x D x H without feet: 1462 x 513 x 840 mm and with feet: 1462 x 513 x 860/880 mm

2 Doors, stainless steel (AISI 430) exterior

3 Doors, anthracite exterior

- Internal volume: 495 L
- Bottle capacity: 489 x 33 cl
- Power consumption: 370 W*
- Dimensions W x D x H without feet: 2002 x 513 x 840 mm and with feet: 2002 x 513 x 860/880 mm

3 Doors, stainless steel (AISI 430) exterior

4 Doors, anthracite exterior

- Internal volume: 630 L
- Bottle capacity: 684 x 33 cl
- Power consumption: 370 W*
- Dimensions W x D x H without feet: 2542 x 513 x 840 mm and with feet: 2542 x 513 x 860/880 mm

4 Doors, stainless steel (AISI 430) exterior

Reference	List price
ECO/22MU	
ECO/22MUCS	
ECO/222MU	
ECO/222MUCS	
ECO/2222MU	
ECO/2222MUCS	

*conditions : Te = -5°C, Tc = 45°C, ambient = 25°C



Glass Doors...



2 Glass doors, anthracite exterior

- Internal volume: 325 L
- Bottle capacity: 294 x 33 cl
- Power consumption: 422 W*
- Dimensions W x D x H without feet: 1462 x 513 x 840 mm and with feet: 1462 x 513 x 860/880 mm
- Locks and illumination fitted as standard

2 Glass doors, stainless steel (AISI 430) exterior



3 Glass doors, anthracite exterior

- Internal volume: 495 L
- Bottle capacity: 489 x 33 cl
- Power consumption: 448 W*
- Dimensions W x D x H without feet: 2002 x 513 x 840 mm and with feet: 2002 x 513 x 860/880 mm
- Locks and illumination fitted as standard

3 Glass doors, stainless steel (AISI 430) exterior



4 Glass doors, anthracite exterior

- Internal volume: 630 L
- Bottle capacity: 684 x 33 cl
- Power consumption: 474 W*
- Dimensions W x D x H without feet: 2542 x 513 x 840 mm and with feet: 2542 x 513 x 860/880 mm
- Locks and illumination fitted as standard

4 Glass doors, stainless steel (AISI 430) exterior

Reference

List price

ECO/22GMU

ECO/22GMUCS

ECO/222GMU

ECO/222GMUCS

ECO/2222GMU

ECO/2222GMUCS

Optional extras



- Extra shelf for use with ECO/22 and ECO/222 (1 door in width)
- Extra shelf for use with ECO/222 and ECO/2222 (2 doors in width)
- Wine rack for use with ECO/22 and ECO/222 (1 door in width)
- Wine rack for use with ECO/222 and ECO/2222 (2 doors in width)
- Shelf / Rack support clip (4-8 pieces per shelf/rack necessary)

000050347

0000150348

004010409

004010410

013010001

*conditions : T_e = -5°C, T_c = 45°C, ambient = 25°C

Eco-Line, under counter cabinets for remote application



Eco-Line cabinets: large storage capacity at a small investment.

Highly efficient bottle cooling cabinets available in anthracite skin plate or stainless steel finish and solid doors or glass doors. Insulation: polyurethane 40 mm. Standard features: electronic thermostat, automatic defrost, exchangeable magnetic gaskets and 2 shelves per door section.

Cooling cabinet for remote application**

Climate class N: functions optimally in surrounding temperatures of up to 32°C / 90°F.
Voltage range: 220-240 V / 50Hz / 1~ - Temperature range: +1° C/+12° C

Solid Doors...

2 Doors, anthracite exterior

- Internal volume: 325 L
- Bottle capacity: 286 x 33 cl
- Power consumption: 86 W*
- Dimensions W x D x H without feet: 1162 x 513 x 840 mm and with feet: 1162 x 513 x 860/880 mm

2 Doors, stainless steel (AISI 430) exterior

3 Doors, anthracite exterior

- Internal volume: 495 L
- Bottle capacity: 480 x 33 cl
- Power consumption: 86 W*
- Dimensions W x D x H without feet: 1702 x 513 x 840 mm and with feet: 1702 x 513 x 860/880 mm

3 Doors, stainless steel (AISI 430) exterior

4 Doors, anthracite exterior

- Internal volume: 630 L
- Bottle capacity: 676 x 33 cl
- Power consumption: 86 W*
- Dimensions W x D x H without feet: 2242 x 513 x 840 mm and with feet: 2242 x 513 x 860/880 mm

4 Doors, stainless steel (AISI 430) exterior

Reference	List price
ECO/22VS	
ECO/22VSCS	
ECO/222VS	
ECO/222VSCS	
ECO/2222VS	
ECO/2222VSCS	

*conditions : Te = -5°C, Tc = 45°C, ambient = 25°C

**For remote application, a remote condensing unit is required (see page 39)



Glass Doors**...



2 Glass doors, anthracite exterior

- Internal volume: 325 L
- Bottle capacity: 286 x 33 cl
- Power consumption: 112 W*
- Dimensions W x D x H without feet: 1162 x 513 x 840 mm and with feet: 1162 x 513 x 860/880 mm
- Locks and illumination fitted as standard

ECO/22GVS



2 Glass doors, stainless steel (AISI 430) exterior

ECO/22GVSCS

3 Glass doors, anthracite exterior

- Internal volume: 495 L
- Bottle capacity: 480 x 33 cl
- Power consumption: 138 W*
- Dimensions W x D x H without feet: 1702 x 513 x 840 mm and with feet: 1702 x 513 x 860/880 mm
- Locks and illumination fitted as standard

ECO/222GVS

3 Glass doors, stainless steel (AISI 430) exterior

ECO/222GVSCS



4 Glass doors, anthracite exterior

- Internal volume: 630 L
- Bottle capacity: 676 x 33 cl
- Power consumption: 164 W*
- Dimensions W x D x H without feet: 2242 x 513 x 840 mm and with feet: 2242 x 513 x 860/880 mm
- Locks and illumination fitted as standard

ECO/2222GVS

4 Glass doors, stainless steel (AISI 430) exterior

ECO/2222GVSCS



Optional extras

- Extra shelf for use with ECO/22 and ECO/222 (1 door in width)
- Extra shelf for use with ECO/222 and ECO/2222 (2 doors in width)
- Wine rack for use with ECO/22 and ECO/222 (1 door in width)
- Wine rack for use with ECO/222 and ECO/2222 (2 doors in width)
- Shelf / Rack support clip (4-8 pieces per shelf/rack necessary)

000050347

0000150348

004010409

004010410

013010001

*conditions : Te = -5°C, Tc = 45°C, ambient = 25°C

**For remote application, a remote condensing unit is required (see page 39)